



6005 Bearing 2D drawings and 3D CAD models

Distributor of NTN Timken NSK Koyo SKF
Ball Bearing 6005 6006 6007 6008 6009 6010 Open
Zz 2RS Bearings for Motorcycle/Engine/Electric
Motor/Pump/Power Generator

Bearing No. 6005

| | |
|-------------------------------|--------------------------|
| Size | 25x47x12 mm |
| Bore Diameter | 25 mm |
| Outer Diameter | 47 mm |
| Width | 12 mm |
| d | 25 mm |
| D | 47 mm |
| B | 12 mm |
| C | 12 mm |
| r min. | 0,6 mm |
| da min. | 29 mm |
| Da max. | 43 mm |
| ra max. | 0,6 mm |
| Weight | 0,08 Kg |
| Basic dynamic load rating (C) | 10,1 kN |
| Basic static load rating (C0) | 5,85 kN |
| (Grease) Lubrication Speed | 15000 r/min |
| (Oil) Lubrication Speed | 18000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | KOYO |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.087 |
| EAN | 0605790044366 |
| | |



China 6204 2rs Bearing Supplier

| | |
|---------------------------------|--|
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 25MM Bore; 47MM Outside Diameter; 12MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.koyousa.com |
| Manufacturer Item Number | 6005 |
| Weight / LBS | 0.191 |
| Bore | 0.984 Inch 25 Millimeter |
| Outer Race Width | 0.472 Inch 12 Millimeter |
| Outside Diameter | 1.85 Inch 47 Millimeter |
| Bearing No. | 6005 |
| r(min) | 0.6 |
| Cr | 12.6 |
| C0r | 5.85 |
| Cu | 0.380 |
| | |



China 6204 2rs Bearing Supplier

| | |
|-------------------|-------|
| f0 | 14.5 |
| Grease lub. | 15000 |
| Oil lub. | 18000 |
| da(min) | 29 |
| Da(max) | 43 |
| ra(max) | 0.6 |
| (Refer.) Mass(kg) | 0.080 |